Dell S series monitors S2740L 27", S2440L 24", S2340L/M 23" and S2240L/M 21.5" Monitors with LED



Charmaine Yeo Displays outbound marketing

RTS date Worldwide: 20th Sept 2012

Dell S series monitors with LED



What are they?

- Dell's range of consumer monitors sporting a beautiful new look:
 - S2240L/M and S2340L/M monitors are virtually borderless
 - S2740L and S2440L monitors have a clean, flush edge-to-edge glass, and are almost frameless
- S2740L is Dell's first 27" consumer monitor
- The S2440L replaces the ST2420L; the S2340L replaces the ST2320L; S2240L replaces the ST2220L
- The suffixes L and M indicate the ports found on each monitor model. The 27" and 24" monitors only come with VGA and HDMI (L suffix); while the 23" and 21.5" monitors have both models with L and M suffixes.
 - L: VGA + HDMI
 - M: VGA + DVI

What makes them different?

- Dell S series monitors redefine elegance and performance in a virtually borderless/ frameless design.
- These consumer series monitors come with advanced panel technologies with ultra-wide viewing angles
- These monitors come with Image Enhance feature designed to improve the visual quality of your onscreen monitors

Target audience

- Gen Y
- Affluent professionals
- Customers buying XPS desktops or notebooks



Dell S series monitors with LED

S series value proposition

The Dell S series maximizes your media entertainment experience with aesthetics and performance. Seamless and intuitive to use, it helps you be efficient and productive, all in a stylish design.

<u>S series messaging</u>

<u>Single sentence description</u>

Experience visual screen brilliance on this amazingly beautiful, virtually borderless Dell S2340L/M 23" monitor (OR S2240L/M 21.5" monitor). Experience visual screen brilliance on this amazingly beautiful, virtually frameless Dell S2740L 27" monitor (OR 2440L 24" monitor).

Short description

Get both beauty and performance on this amazingly beautiful, virtually borderless Dell S2340L/S2240 monitor OR virtually frameless Dell S2740/2440 monitor. Visually brilliant, the S series monitors can enhance your multimedia experience with their full HD resolution, high color gamut and mega dynamic contrast ratio of 8 million:1 (typical) – offering you vivid image clarity and colors so rich, they simply pop off the screen! The fast screen response times on the S series monitors also help minimize motion blur and their 178°/178° (typical) ultra-wide viewing angles simply make watching movies and playing games an amazing experience.



Dell S series monitors with LED

Redefining elegance and performance

Key messaging	What they are	Benefits
Seamless viewing experience and elegant	• Virtually borderless with technically- brilliant glossy panel design (S2340L/M & S2240L/M)	• Redefines your viewing experience with a virtually borderless design, providing you with the ultimate big picture and sense of infinity by eliminating the space between the panel and bezel.
craftsmanship	Frameless design on a glossy screenDesign that redefines elegance	• Provides you with a seamless viewing experience with their flushed edge-to- edge glass a clean finish that boasts of fine craftsmanship on a glossy screen.
		• From monitor panel, to the design of the riser, right up to the Dell chrome badge, the Dell S series redefines elegance.
		• Thin monitors with great looks exude a modern and contemporary appeal - all in a stylish design.
Remarkable screen performance	• Ultra-wide viewing angle of 178°/178° (typical)	• An ultra-wide viewing angle facilitates collaborative viewing, and can improve your work productivity
performance	 Superb clarity, color accuracy and consistency 	• In-plane switching and Vertical alignment panel technologies offer superb on- screen clarity and color accuracy and consistency across a wide viewing angle.
	Image Enhance capability	• Image Enhance feature enhances your picture quality by sharpening the images, improving the color hues, and boosting the color contrast.
	• Dell Display Manager – Auto mode	• The new Dell Display Manager comes with an Auto mode option that allows you to set your preferred optimal preset mode to your active applications (e.g. Movie, Multimedia, Game, Text, Warm, Cool, Custom Color)
	• Full HD 1920 x 1080 (max) resolution with 16:9 aspect ratio	• Get sharp, vivid, cinematic-quality images with full high-definition resolution that supports a 16:9 widescreen format.
	• Mega dynamic contrast ratio at 8million:1 (typical)	•Experience amazing color details such as deep blacks and bright whites while viewing photos and videos.
	• Wide color gamut* (typical) - S27@ 84%, S24@ 86%, S23 & S22 @ 82% *Color gamut (typical) is based on CIE1976 (84%/89%/82%/82%) and CIE1931 (72%) test standards.	• Enjoy brilliant color performance with the S series' ability to produce a wide range of colors.

Dell S series monitors with LED

Key messaging	What they are	Benefits
Great usability and comfort	• Tilt (for all models)	• Maximizes your viewing comfort by allowing you to adjust to your preferred angle
	Cable management	A neater and clutter-free desktop
	• HDMI & VGA ports (S2740L has	VGA connector facilitates easy connection to most PCs.
	additional USB port)	• HDMI port gives you uncompromised high quality video and audio performance
Energy efficient	 Made of environmentally responsible materials Arsenic-free glass and mercury-free LED panel 	• These less hazardous materials help make the monitors easy to recycle, and lower your power consumption
	Meet latest environmental standards -ENERGY STAR® - EPEAT Silver	• Meet strict energy efficiency guidelines set by the EPA and US Department of Energy, helping you reduce your energy bills and improve home comfort. Have environmentally preferable product design and management.
	• Power management software: PowerNap	• PowerNap software helps to dim the monitor to its minimum brightness level or puts it into sleep mode when not in use, helping you be energy efficient



Displays

Dél



New features

Dell Display Manager

Enjoy great productivity with the easy-to-use Dell Display Manager – your one stop software application for the following features:

Auto Mode

With Auto mode, the color settings of applications now appear how you want them to. Simply select the optimal preset mode of your choice for specific applications and the active application will use the preset mode you have picked. Eg. select Multimedia mode for Internet Explorer, so that opening Internet Explorer thereafter will enable you to view your internet pages in the multimedia mode's color settings.

PowerNap

Conserve energy with the S series monitors' PowerNap feature, which dims the monitor to its minimum brightness or puts it in to sleep mode when not in use.

Easy Arrange (only available on the S2740L and S2440L monitors)

Improve your productivity with the Easy Arrange software, which organizes your monitor screen by arranging/ tiling your applications side by side, so that you can view multiple application windows at one glance.

Simply select your preferred available layout on Easy Arrange, and drag and drop the specific applications into your preferred grid location.







Displays

New features



Without Image Enhance

With Image Enhance

Dell S2340L		Energy Use IIIIIIIII 10000000
- Drightness/Contrast	Input Color Format	▶ RGB
主 Auto Adjust	Preset Modes	▶ Standard
← Input Source	Image Enhance	▶ On
Color Settings	Reset Color Settings	
Display Settings		
🛱 Other Settings		
+ Personalize		
	Consumer 1 Series (1)	Foreigner Sorres City of Cart
Resolution : 1280x800@		Maximum Resolution : 1920x1080@60Hz

Image Enhance

Image Enhance feature enhances your picture quality by sharpening the images, improving the color hues, and boosting the color contrast.

Key difference from existing models

	S2440L/ S2340L/ S2240L New!	ST2420L/ ST2320L/ST2220L
Panel type and backlight	S2440: VA with LED backlight S2340 & S2240: In-plane switching with LED backlight	TN with LED backlight
Viewing angle (vertical/horizontal)	178°/178°	160°/170°
Contrast ratio (typical)	S2440: 5,000:1; S2340 & S2240: 1000:1	1,000:1
Color gamut (typical) based on CIE 1976 test standards	86%/ 82%/ 82%	81%/ 78%/ 78%
Image Enhance feature	Yes	No
Power consumption (normal operation, typical)	18W/ 19W/ 18W	20W/ 24W/ 20W
Power consumption (active-off mode)	< 0.5 W	< 1 W

Key features to upsell S2440L/ S2340L/ S2240L from ST2420L/ ST2320L/ST2220L

S2440L/ S2340L/ S2240L are/have:

- Ultra-wide viewing angles color of images remain accurate and consistent no matter which angle you view the monitor from
- Higher contrast ratios result in better display of variations in gray tones, better color imaging, richer and more accurate colors
- Image Enhance feature enhances picture quality by sharpening images, improving the color hues and color contrast.
- Low power consumption helps you save more energy by having a lower power consumption than their predecessors in the typical and active-off modes

Tech specs call out







Dell S2740L 27" Monitor with LED

- 27-inch wide (69cm) VIS with LED backlight
- Full High definition, 1920 x 1080 at 60 Hz
- In-plane switching panel technology
- 178°/178° (vertical/horizontal) wide viewing angle
- 8million:1 (typical) mega dynamic contrast ratio
- VGA, DVI-D (HDCP), HDMI and USB ports

Dell S2440L 24" Monitor with LED

- 24-inch wide (61cm) VIS with LED backlight
- Full High definition, 1920 x 1080 at 60 Hz
- Vertical alignment panel technology
- 178°/178° (vertical/horizontal) wide viewing angle
- High contrast ratio of 5000: 1 (typical)
- 8million:1 (typical) mega dynamic contrast ratio

Tech specs call out





Dell S2340L/M 23" Monitor with LED

- 23-inch wide (58cm) VIS with LED backlight
- Full High definition, 1920 x 1080 at 60 Hz
- In-plane switching panel technology
- 178°/178° (vertical/horizontal) wide viewing angle
- 8 million:1 (typical) mega dynamic contrast ratio

Dell S2240L/M 21.5" Monitor with LED

- 21.5-inch wide (55cm) VIS with LED backlight
- Full High definition, 1920 x 1080 at 60 Hz
- In-plane switching panel technology
- 178°/178° (vertical/horizontal) wide viewing angle
- 8 million:1 (typical) mega dynamic contrast ratio

Key features (for SuperView online)

• Amazingly beautiful. Virtually frameless (for S2740L and S2440L) See the big picture on the amazingly beautiful, virtually frameless S2740L and S2440L monitors.

• Amazingly beautiful. Virtually borderless (for S2340L/M and S2240L/M monitors)

Experience infinity with the amazingly beautiful, virtually borderless S2340L/M and S2240L/M monitors.

Clear and vivid images

Enjoy sharp, vivid, cinematic-quality images on its full high-definition 1920 x 1080 (max) resolution that supports a 16:9 widescreen format. With the new Image Enhance feature, your pictures onscreen now look better with improved clarity, color hues and color contrast.

Seamless viewing experience

Experience amazing color details such as deep blacks and bright whites while viewing photos and videos with its 8 million:1 (typical) mega dynamic contrast ratio.

Awesome colors

A wide color gamut means you get brilliant color performance with the monitor's ability to produce a wide range of colors.

Eco-design

Designed to be environmentally conscious, the monitors are made of less hazardous materials such as arsenic-free and mercury-free LED panel, and are ENERGY STAR® and EPEAT Silver compliant.

• Well connected (*Pls refer to slides 11 to 14 for types of ports available for each model)

Seamlessly connect to your desktop, laptop or gaming console with VGA, DVI (HDCP), and HDMI ports.

• For your viewing pleasure

Designed with your ultimate comfort in mind, the S series monitors allow you to easily tilt the panel up to 4° forward or 21° backward.

Product specifications Dell S2740L 27" Monitor with LED

		voltage/ Current
Display		Power c
Viewable image size (diagonal)	68.6 cm (27 inches)	operatic
Horizontal Vertical	597.9 mm (23.54 inches) 336.3 mm (13.24 inches)	Power c off mod
Maximum resolution	1920 x 1080 at 60 Hz	Dimen
Aspect ratio	16:9	Height
Pixel pitch	0.311 mm	Width
Brightness (typical)	270 cd/m ²	Depth
Color gamut (typical)	84%1	
Color depth	16.7 million colors	Weight Weight
Contrast ratio (typical)	1,000:1	assembl VESA mo
Dynamic contrast ratio (typical)	8 million:1	no cable
Viewing angle (typical) vertical/horizontal	178°/178°	Weight v and cab
Response time (typical)	7 ms with overdrive (gray to gray)	Weight
Panel type	In-plane switching	Enviror
Backlight	LED	ENERGY
Connectivity		Service
Connectors	VGA, 2 x USB, DVI-D (HDCP), HDMI	1 year Lii 3 years L
Design Features		Service ³ (
Stand	Tilt, and built-in cable management	¹ Color gamut ² For a copy of 78682 or see <u>3</u> ³ Advanced Exe
Security	Security lock slot and stand lock (security lock and M3x6mm screw for stand lock not included)	diagnosis. Fee
VESA mounting support (wall mount sold separately)	100 mm x 100 mm	

Power	
AC input voltage/frequency/ Current (max)	100 to 240 VAC/50 or 60 Hz ± 3 Hz/1.2 A
Power consumption (normal operation, typical)	21 W
Power consumption (active- off mode)	<0.5 W
Dimensions (with stand)	
Height	458.7 mm (18.06 inches)
Width	641.9 mm (25.27 inches)
Depth	215.8 mm (8.50 inches)
Weight	
Weight without stand assembly (For wall mount or VESA mount considerations – no cables)	5.28 kg (11.62 lbs)
Weight with stand assembly and cables	7.56 kg (16.67 lbs)
Weight with packaging	9.18 kg (20.24 lbs)
Environmental compliance	
ENERGY STAR, EPEAT Silver	
Service and warranty	
1 year Limited Hardware Warranty ² (USA & LAR) 3 years Limited Hardware Warranty (rest of world); Advanced Exchange Service ³ (All regions)	
 ¹ Color gamut (typical) is based on CIE1976 (84% of NTSC) and CIE1931 (72%) test standards. ² For a copy of the Limited Hardware Warranty, write to Dell USA LP, Attn: Warranties, One Dell Way, Round Roc 78682 or see <u>www.dell.com/warranty</u>. ³ Advanced Exchange Service: Replacement part/unit dispatched, if needed, following completion of phone/onli diagnosis. Fee charged for failure to return defective unit. Availability varies. Other conditions apply. 	

Displays

Product specifications

Dell S2440L 24" Monito	or with LED	Power	Power		
Display		AC input voltage/frequency/	100 to 240 VAC/50 or 60 Hz ± 3 Hz/1.2 A		
Viewable image size (diagonal)	60.97 cm (24 inches)	Current (max)			
Horizontal Vertical	531.36 mm (20.92 inches) 298.89 mm (11.77 inches)	Power consumption (normal operation, typical)	18 W		
Maximum resolution	1920 x 1080 at 60 Hz	Power consumption (active-	<0.5 W		
Aspect ratio	16:9	Dimensions (with stand)			
Pixel pitch	0.277 mm	Height	417.9 mm (16.45 inches)		
Brightness (typical)	250 cd/m ²				
Color gamut (typical)	86%1	Width	567.4 mm (22.34 inches)		
Color depth	16.7 million colors	Depth	190.8 mm (7.51 inches)		
Contrast ratio (typical) 5,000:1		Weight			
Dynamic contrast ratio (typical)	8 million:1	Weight without stand assembly	3.60 kg (7.94 lbs)		
Viewing angle (typical) vertical/horizontal	178°/178°	Weight with stand assembly	4.95 kg (10.91 lbs)		
Response time (typical)	6 ms with overdrive (gray to gray)	and cables Weight with packaging	5.91 kg (13.03 lbs)		
Panel type	VA	Environmental compliance			
Backlight LED		ENERGY STAR, EPEAT Silver			
Connectivity					
Connectors VGA, HDMI		Service and warranty			
Design Features		1 year Limited Hardware Warranty ² (USA & LAR) 3 years Limited Hardware Warranty (rest of world); Advanced Exchange Service ³ (All regions) ¹ Color gamut (typical) is based on CIE1976 (89% of NTSC) and CIE1931 (72%) test standards. ² For a copy of the Limited Hardware Warranty, write to Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX			
Stand	Tilt				
Security	urity Security lock slot		78682 or see <u>www.dell.com/warranty</u> . ³ Advanced Exchange Service: Replacement part/unit dispatched, if needed, following completion of phone/online diagnosis. Fee charged for failure to return defective unit. Availability varies. Other conditions apply.		
	<u> </u>		\frown		



Product specifications

Dell S2340L/M 23" Monitor with LED

Display	AC input voltage/freque	
Viewable image size (diagonal)	58.42 cm (23 inches)	Current (max)
Horizontal Vertical	509.18 mm (20.05 inches) 286.41 mm (11.28 inches)	Power consun operation, typi
Maximum resolution	1920 x 1080 at 60 Hz	Power consun off mode)
Aspect ratio	16:9	Dimensions
Pixel pitch	0.265 mm	Height
Brightness (typical)	250 cd/m ²	
Color gamut (typical)	82%1	Width
Color depth	16.7 million colors	Depth
Contrast ratio (typical)	1,000:1	Weight
Dynamic contrast ratio (typical)	8 million:1	Weight withou assembly
Viewing angle (typical) vertical/horizontal	178°/178°	Weight with st
Response time (typical)	7 ms with overdrive (gray to gray)	cables, adapte Weight with pa
Panel type	In-plane switching	Environmen
Backlight	LED	
Connectivity		ENERGY STAR, E
Connectors (S2240L)	VGA & HDMI	Service and
Connectors (S2240M)	VGA & DVI (HDCP)	1 year Limited H 3 years Limited
Design Features		Service ³ (All regi
Stand	Tilt	 ¹ Color gamut (typical) is ² For a copy of the Limite 78682 or see <u>www.dell.c</u> ³ Advanced Exchange Sei diagnosis. Fee charged f
Security	Security lock slot	

Power	
AC input voltage/frequency/ Current (max)	100 to 240 VAC/50 or 60 Hz ± 3 Hz/1.2 A
Power consumption (normal operation, typical)	19 W
Power consumption (active- off mode)	<0.5W
Dimensions (with stand)	
Height	398.9 mm (15.70 inches)
Width	532.2 mm (20.95 inches)
Depth	175.8 mm (6.92 inches)
Weight	
Weight without stand assembly	2.95 kg (6.50 lbs)
Weight with stand assembly, cables, adapter, and dongle	3.91 kg (8.62 lbs)
Weight with packaging	4.95 kg (10.91 lbs)
Environmental compliance	
ENERGY STAR, EPEAT Silver	
Service and warranty	
1 year Limited Hardware Warranty ² (USA & LAR) 3 years Limited Hardware Warranty (rest of world); Advanced Exchange Service ³ (All regions)	
¹ Color gamut (typical) is based on CIE1976 (82% of NTSC) and CIE1931 (72%) test standards. ² For a copy of the Limited Hardware Warranty, write to Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 78682 or see <u>www.dell.com/warranty</u> . ³ Advanced Exchange Service: Replacement part/unit dispatched, if needed, following completion of phone/online diagnosis. Fee charged for failure to return defective unit. Availability varies. Other conditions apply.	
Displays	

Product specifications

Dell S2240L/M 21.5" Monitor with LED

Display		AC inp voltag
Viewable image size (diagonal)	54.62 cm (21.5 inches)	Currei
Horizontal Vertical	476.06 mm (18.76 inches) 267.78 mm (11.85 inches)	Power operat
Maximum resolution	1920 x 1080 at 60 Hz	Power off mo
Aspect ratio	16:9	Dime
Pixel pitch	0.248 mm	Heigh
Brightness (typical)	250 cd/m ²	Width
Color gamut (typical)	82%1	
Color depth	16.7 million colors	Depth
Contrast ratio (typical)	1,000:1	Weig
Dynamic contrast ratio (typical)	8 million:1	Weigh
Viewing angle (typical) vertical/horizontal	178°/178°	Weigh cables
Response time (typical)	7 ms with overdrive (gray to gray)	Weigh
Panel type	In-plane switching	Envir
Backlight	LED	ENERG
Connectivity		Servio
Connectors (S2240L)	VGA & HDMI	1 year
Connectors (S2240M)	VGA & DVI (HDCP)	3 years
Design Features		¹ Color gam
Stand	Tilt	² For a copy 78682 or se ³ Advanced I diagnosis. F
Security	Security lock slot	

	Power		
	AC input voltage/frequency/ Current (max)	100 to 240 VAC/50 or 60 Hz ± 3 Hz/1.2 A	
1	Power consumption (normal operation, typical)	18 W	
	Power consumption (active- off mode)	<0.5W	
	Dimensions (with stand)		
	Height	380.2 mm (14.97 inches)	
	Width	499.1 mm (19.65 inches)	
	Depth	175.8 mm (6.92 inches)	
	Weight		
	Weight without stand assembly	2.60 kg (5.73 lbs)	
	Weight with stand assembly, cables, adapter, and dongle	3.69 kg (8.13 lbs)	
	Weight with packaging	4.60 kg (10.14 lbs)	
	Environmental compliance		
	ENERGY STAR, EPEAT Silver		
	Service and warranty		
	1 year Limited Hardware Warranty ² (USA & LAR) 3 years Limited Hardware Warranty (rest of world); Advanced Exchange Service ³ (All regions)		
	 ¹ Color gamut (typical) is based on CIE1976 (82% of NTSC) and CIE1931 (72%) test standards. ² For a copy of the Limited Hardware Warranty, write to Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 78682 or see <u>www.dell.com/warranty</u>. ³ Advanced Exchange Service: Replacement part/unit dispatched, if needed, following completion of phone/online diagnosis. Fee charged for failure to return defective unit. Availability varies. Other conditions apply. 		
	Displays		