

SPECIFICATIONS

DISPLAY

Panel Size: 55"
Type/Tech: TFT LCD (IPS type,DLED Backlight)
Display Area (mm): 1209.6 (H) * 680.4 (V)
Aspect Ratio: 9:16
Native Resolution: 3840 x 2160
Colors: 1.07B
Brightness: 350 nits (typ.)
Contrast Ratio: 1200:1 (typ.)
Response Time: 9 ms (typ. G to G)
Viewing Angles: H = 178, V = 178 typ.
Backlight Life: 30,000 Hours Typ.
Surface Treatment: Anti-glare
Orientation: Portrait

TOUCH

Type/ Tech: IR Recognition
Touch Resolution: 32768 x 32768
Touch Point: 10 Points

STORAGE

eMMC 16GB

INPUT

HDMI: (1.4) x2
RGB / VGA: x1
Audio: x1 PC audio(3.5 mm)
RS232: x1

OUTPUT

Audio: x1 (Earphone out)

LAN

RJ45: x1

USB

Type A: x3 (2.0 x 1, 3.0 x 2)
Type B: x1 (for touch module)

SPEAKERS

10W x 2

COMPATIBILITY

RGB PC/HDMI PC: 1920x1080 @60Hz
HDMI: 2160 x 3840 @60Hz

ANDROID VERSION

5.0.1

MULTIMEDIA

Image: JPG, BMP, PNG

Video: AVI, MPG, MPEG, DAT, MP4, TS, RM, RMVB, MKV, MOV

Audio: MP3, AAC

BUNDLE SOFTWARE

vSignage

POWER

Voltage: 100-240VAC +/- 10% Wide Range

Consumption: Normal 117 W, Max 150 W (max.)

< 0.5W (Off)

OPERATING CONDITIONS

Temperature (° C): 0°C to 40°C

Humidity: 20% ~ 80% non-condensing

DIMENSIONS (W X H X D)

Physical (inch / mm): 32.28 x 74.8 x 17.71 in/820 x 1900 x 450 mm

Packaging (inch / mm): 38.7 x 79.37 x 24.33 in/983 x 2016 x 618 mm

WEIGHT

Net (lb / kg): 154.32 lbs/70 kg

Gross (lb / kg): 187.39 lbs/85 kg

REGULATIONS

cTUVus, FCC, BSMI

PACKAGE CONTENTS

1. Power Cord
2. Remote control with battery
3. Quick Start Guide
4. User Guide CD
5. Key

*Actual content may differ from market to market
