

# Specs

---

## Camera

- Sensor: 1/2.5"Sony Exmor 4K CMOS sensor
- Frame rate: 4K 30fps; 1080p , 720p , 960x540, 848x480, 800x448, 640x480, 640x360, 424x240, 320x240, 320x180 at up to 60fps
- 120° Wide field of view
- Lens iris, focus, zoom: fixed
- AE, white balance: auto, manual override by PTZApp
- Minimum working distance: 80cm
- Back light compensation and 2D noise reduction technology for optimizing light balance in different conditions
- Standard tripod screw holes

\*Get notified while this function is available, please send request to our technical support to leave your contact information. <http://www.aver.com/technical-support>

---

## Zoom, Pan, and Tilt Movement

- Zoom: up to 4X leveraging 4K sensor (not available in 4K or 60fps)
  - Pan and tilt: when zoomed in leveraging 4K sensor
- 

## Microphone

- 1 uni-directional microphones
- Frequency response: 100~12K Hz
- Sensitivity: -37dB

\*This function may not be available in certain regions

---

## Connectivity

- USB Type C connector
  - Reset button
  - DC jack for power adapter (for USB 2.0 connection)
- 

## Video Format

- YUV, MJPEG
- 

## USB

- 2.0, 3.1 Gen1 type C
  - UVC (USB Video Class) 1.1
- 

## Control

- IR remote control (optional accessory, compatible with CAM540)
  - UVC / plug-and play
  - PTZApp
- 

## Security and Mount

- Built-in TV mount (above TV, up to 46 mm deep)
  - Kensington slot
  - 1/4" tripod mounting screw
- 

## System Requirement\*

- Windows 7/10
  - Mac OS X 10.7 or higher
  - Android 7.0 or above
- 

## Hardware Spec\*

- 2.4GHz Intel® Core 2 Duo processor
  - 2GB RAM or more
  - USB 2.0 port and above (USB 3.1 required for 4K or 60fps)
- 

## Power Supply

- Consumption: USB 3.1 Supports up to 4K : 5V/0.9A;
  - USB 2.0 Supports up to 2K: 5V/0.5A
- 

## Environmental Data

- Operation temperature: 0 ~40°C
  - Operation humidity: 20% ~80%
  - Storage temperature: -20 ~60°C
  - Storage humidity: 20% ~80%
- 

## Dimension

- Package dimensions: 138 x 138 x 149 mm
  - Package weight: 0.622 kg
  - Camera (folded): 60 x 60 x 75 mm
  - Camera weight: 0.251 kg
- 

## Package Contents

- USB3.0 4K Camera
  - USB3.1 type-C to type-A Cable (6ft)
  - Quick-start guide
- 

## Optional Accessories

- Wall mount
  - Remote control (compatible with CAM540)
  - Power adapter (for USB 2.0)
- 

## Warranty\*\*

- Camera: 3+2 year
  - Accessories: 1 year
- 

## Compatible Applications

- ZOOM, Microsoft® Teams, Skype for Business, Skype™, Google Hangouts, Intel® Unite™, RingCentral, BlueJeans, V-Cube, LiveOn, CyberLink U Meeting®, TrueConf, Adobe Connect, Cisco WebEx®, Fuze, GoToMeeting™, Microsoft® Lync™, Vidyo, vMix, WebRTC, Wirecast, XSplit
- 

## Free Applications for Meeting Collaboration (Free Apps support on Windows® and Mac® computers)

PTZApp

- Compatible with Skype™ Plugin for answering and hanging up via remote control
- Upgrade firmware automatically or manually
- Control camera
- Set parameters and adjust camera image
- Diagnose operating status
- View live video

#### **EZLive**

- Real-time streaming / annotating / snapshots / video recording
- \*Suggested to have 2GB HDD storage for saving recorded video clips
-