

Video

Video Processing

4:2:2 (Y/Pb/Pr), 8-bit

Input Connectors

INPUT 1--3: HDMI type A x 3

*HDCP Supported

INPUT 4: HDMI type A

* HDCP Supported

* Multi-format Supported

Output Connectors

OUTPUT 1--2: HDMI type A x 2

* HDCP Supported

Input Formats

INPUT 1--3

720/59.94p, 720/60p *1, *3

720/50p *1, *4

1080/59.94i, 1080/60i, 1080/59.94p, 1080/60p, 1080/29.97p, 1080/30p *2, *3

1080/50i, 1080/50p, 1080/25p *2, *4

1080/23.98p, 1080/24p *2

* The input interlaced video signal is converted to progressive video signal by internal processing.

*1 SYSTEM FORMAT = 720p

*2 SYSTEM FORMAT = 1080i or 1080p

*3 FRAME RATE = 59.94 Hz

*4 FRAME RATE = 50 Hz

INPUT 4

480/59.94i, 480/59.94p, 720/59.94p, 720/60p, 1080/59.94i, 1080/60i, 1080/59.94p, 1080/60p,

1080/29.97p, 1080/30p *1

576/50i, 576/50p, 720/50p, 1080/50i, 1080/50p, 1080/25p *2

1080/23.98p, 1080/24p

VGA (640 x 480/60 Hz), SVGA (800 x 600/60 Hz), XGA (1024 x 768/60 Hz)

WXGA (1280 x 800/60 Hz), SXGA (1280 x 1024/60 Hz)

FWXGA (1366 x 768/60 Hz), SXGA+ (1400 x 1050/60 Hz)

UXGA (1600 x 1200/60 Hz), WUXGA (1920 x 1200/60 Hz)

* The refresh rate is the maximum value of each resolution.

* Conforms to CEA-861-E, VESA DMT Version 1.0 Revision 11.

* 1920 x 1200/60 Hz: Reduced blanking

* The input interlaced video signal is converted to progressive video signal by internal processing.

*1 FRAME RATE = 59.94 Hz

*2 FRAME RATE = 50 Hz

Still Image:

Bitmap File (.bmp) Maximum 1920 x 1080 pixels, 24-bit color, uncompressed.

PNG File (.png) Maximum 1920 x 1080 pixels, 24-bit color

* It can store up to 4 files in the internal memory.

* PNG alpha channel not supported.

Output Formats

OUTPUT 1--2:

720/59.94p *1, *4

720/50p *1, *5

1080/59.94i *2, *4

1080/50i *2, *5

1080/59.94p *3, *4

1080/50p *3, *5

*1 SYSTEM FORMAT = 720p

*2 SYSTEM FORMAT = 1080i

*3 SYSTEM FORMAT = 1080p

*4 FRAME RATE = 59.94 Hz

*5 FRAME RATE = 50 Hz

Video Effects

Transition: CUT, MIX (DISSOLVE/FAM/NAM), WIPE (8 types)

Composition: PinP (SQUARE, CIRCLE, DIAMOND), SPLIT (2 types), Keyer (Luminance key, Chroma key), DSK (Luminance key, Chroma key)

Other: Flip horizontal, Flip vertical, Still image capture, Still image playback, Output fade (Audio, Video: WHITE or BLACK), Test pattern output

Audio

Audio Processing

Sample rate: 24 bits/48 kHz

Audio formats

Linear PCM, 24 bits/48 kHz, 2 ch

Input Connectors

INPUT 1--4: HDMI Type A x 4

AUDIO IN 1--2: XLR-3-31 type (balanced, phantom power DC 48 V, 14 mA Max)

LINE IN: RCA phono type

MIC/AUX IN: Stereo miniature phone type (PLUG-IN power)

Output Connectors

OUTPUT 1--3: HDMI Type A x 2

AUDIO OUT L, R: 1/4-inch TRS phone type

PHONES: Stereo miniature phone type

Nominal Input Level

AUDIO IN 1--2: -60 to +4 dBu (Maximum input level: +24 dBu)

LINE IN: -10 dBu (Maximum input level: +10 dBu)

MIC/AUX IN: -51 to -10 dBu (Maximum input level: +10 dBu)

Input Impedance

AUDIO IN 1--2: 10 k ohms

LINE IN: 15 k ohms

MIC/AUX IN: 10 k ohms

Nominal Output Level

AUDIO OUT L, R: +4 dBu (Maximum output level: +24 dBu)

PHONES: 72 mW + 72 mW (32 ohms load)

Output Impedance

AUDIO OUT L, R: 600 ohms

PHONES: 10 ohms

Audio Effects

Delay, High pass filter, De-Esser, Compressor, Noise gate, Equalizer, Limiter, Reverb, Test tone output

Others

Other Connectors

USB MEMORY: USB A type (for USB flash drive)

REMOTE: USB B type (for remote control)

RS-232: DB-9 type (male, for remote control)

TALLY: DB-9 type (female, for TALLY output)

Other Functions

Preset memory (8 types)

Panel lock function

EDID emulator

Auto switching

Auto input detect

Power Supply

AC adaptor

Current Draw

2.1 A

Power Consumption

25.2 W

Operation Temperature

+0 to +40 degrees Celsius

+32 to +104 degrees Fahrenheit

Dimensions

316 (W) x 121 (D) x 65 (H) mm

12-1/2 (W) x 4-13/16 (D) x 2-9/16 (H) inches

Weight (excluding AC adaptor)

1.4 kg

3 lbs 2 oz

Accessories

Startup Guide

Leaflet "USING THE UNIT SAFELY"

AC adaptor

Power cord

* 0 dBu = 0.775 Vrms