

Video

Input Connectors

HDMI IN connector: HDMI type A

* Multi-format Supported

* HDCP Not Supported

Output Connectors

USB STREAM port: USB 3.0 B type

Input Formats

480/59.94i, 576/50i, 480/59.94p, 576/50p, 720/59.94p, 720/50p, 1080/59.94i, 1080/50i, 1080/59.94p, 1080/50p, VGA (640 x 480/60 Hz), SVGA (800 x 600/60 Hz), XGA (1024 x 768/60 Hz), HD (1280 x 720/60 Hz), WXGA (1280 x 800/60 Hz), SXGA (1280 x 1024/60 Hz), FWXGA (1366 x 768/60 Hz), SXGA+ (1400 x 1050/60 Hz), UXGA (1600 x 1200/60 Hz), FHD (1920 x 1080/60 Hz)

* The refresh rate is the maximum value of each resolution.

* Conforms to VESA DMT Version 1.0 Revision 11.

USB Video Output Format

YUY2 (Uncompressed)

USB Video Output Resolution

1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200, 1600 x 900, 1440 x 900, 1366 x 768, 1360 x 768, 1280 x 1024, 1280 x 960, 1280 x 800, 1280 x 720, 1152 x 864, 1024 x 768, 1024 x 576, 960 x 540, 856 x 480, 800 x 600, 768 x 576, 720 x 576, 720 x 480, 640 x 480, 640 x 360, 320 x 240

* The maximum frame rate is 60 fps.

Audio

Audio formats

HDMI IN connector: Linear PCM, 48 kHz / 44.1 kHz, 24 bits / 20 bits / 16 bits, stereo

USB STREAM port: Linear PCM, 48 kHz, 16 bits, stereo

Input Connectors

HDMI IN connector: HDMI type A

AUX IN jack: Stereo miniature phone type

Output Connectors

USB STREAM port: USB 3.0 B type

Nominal Input Level

AUX IN jack: -10 dBu (Maximum input level: +8 dBu)

Input Impedance

AUX IN jack: 10 k ohms

Others

Power Supply

Supplied from the computer via USB

Current Draw

500 mA

Operation Temperature

+0 to +40 degrees Celsius

+32 to +104 degrees Fahrenheit

Dimensions

90 (W) x 37 (D) x 23 (H) mm

3-9/16 (W) x 1-1/2 (D) x 15/16 (H) inches

Weight (excluding AC adaptor)

96 g

4 oz

Accessories

Owner's Manual

USB 3.0 Cable

* 0 dBu = 0.775 Vrms

