DISPLAY		
DISPLAY SIZE (IN.)	VIEWABLE AREA (IN.)	
55	54.6	
LIGHT SOURCE	RESOLUTION	
DLED	3840 x 2160	
PANEL TYPE	STATIC CONTRAST RATIO	
IPS-Type	1,200:1	
BACKLIGHT LIFE (HOURS)	BRIGHTNESS	
40,000	350 cd/m2	
RESPONSE TIME (TYPICAL GTG)	BEZEL WIDTH (IN.)	
9ms	0.55 (uniform)	
BEZEL WIDTH (MM)	VIEWING ANGLES	
13.9 (uniform)	178° horizontal, 178° vertical	

PANEL SURFACE

Hard Coat - Anti-Glare, 3% Haze, 2H with anti-glare treatment

EMBEDDED PLAYER		
MEDIA PLAYER TYPE	GPU	
Yes	Dual-core MaliG51 MP2	
СРИ	CPU PROCESSOR SPEED	
2 x Dual-core Processors - Cortex A73 + A53	1.4GHz	
MEMORY	STORAGE	
3GB DDR4	16GB eMMC	

AUDIO		
INTERNAL SPEAKERS		
10W (x2)		

OPERATION RATING

24/7

COMPATIBILITY		
PC RESOLUTION (MAX)	MAC® RESOLUTION (MAX)	
3840 x 2160	3840 x 2160	

WEIGHT (IMPERIAL)		
NET (LBS)	GROSS (LBS)	
37.1	52.8	
WEIGHT	(METRIC)	
NET (KG)	GROSS (KG)	
16.8	23.9	
DIMENSIONS (IMPERIAL) (WXHXD)		
PACKAGING (IN.)	PHYSICAL (IN.)	
55.9 x 35.8 x 9.7	48.9 x 28.1 x 2.9	
DIMENSIONS (N	METRIC) (WXHXD)	
PACKAGING (MM)	PHYSICAL (MM)	
1420.0 x 910.0 x 245.0	1243.2 x 714.0 x 74.8	
MC	DUNT	
VESA COMPATIBLE	SCREW SIZE	
400 x 400 mm	M6	
GEN	NERAL	
AV CONTROL	WARRANTY	
AMX Certified, Crestron Certified (Version 1.0), Extron Certified	3-year limited warranty on parts, labor and backlight, onsite warranty	
RECYCLE/DISPOSAL	PACKAGE CONTENTS	
Please dispose of in accordance with local, state or federal laws.	CDE5520, Remote control with batteries, Quick Start Guide, Power cable (1.8m), HDMI (1.8m) and RS232 cable (1.8m)	
REGULATIONS		
cULus, FCC, Energy Star, RoHS, TUV Mexico, Mexico Energy		