

## Cabinet

**Pixel Configuration** SMD 3-IN-1 LED

**Pixel Pitch Category** P1.8

**Pixel Pitch** 1.875 mm

**Modules Component** 2 × 2

**Dimensions (W × H × D)** 480 mm × 540mm × 54 mm (18.90" × 21.26" × 2.12")

**D)**

**Resolution** 256 x 288

**Area** 0.2592 m<sup>2</sup>

7KG (15.43lb)

**Pixel Density** 284444 dots/m<sup>2</sup>

**Lamp Board Housing** no housing

**Cabinet Material** Die-cast aluminum

**Maintenance Method** Front maintenance for all components

**Cabinet Flatness** 0.1 mm

**Protection Level** Front protection level IP5X

## Display

**White Balance** 800 cd/m<sup>2</sup>

**Brightness**

**Color Temperature** 3000 K to 10000 K adjustable

**Viewing Angle** Horizontal 160°, vertical 160°

**Contrast Ratio** ≥ 5000:1

**Color Uniformity** ≤ ± 0.003Cx, Cy

**Brightness Uniformity** ≥ 97%

**Average Consumption** < 200 W/m<sup>2</sup>

---

### **Working Environment**

**Working Temperature** -10-40 °C

---

**Working Humidity** 10%~80%RH

---

**Storage Humidity** 10%~80%RH

---

**Storage Temperature** -20~60 °C

---

### **General**

**Gross Weight** 40 Kg (88.2 lb)

---

**Package Dimension** 598mm × 467mm × 763mm (23.54" × 18.38" × 30.04")

**(W × H × D)** 4in1

---

**Lifespan** Lamp 100,000 hours

---