

Cabinet

Area 0.3072 m²

Cabinet Flatness 0.1 mm

Cabinet Material Die-cast aluminum

Dimensions (W × H × D) 640 mm × 480 mm × 69 mm (25.19" × 18.90" × 2.71")

D)

Lamp Board Housing no housing

Maintenance Method Front maintenance for all components

Modules Component 3 × 2

Pixel Configuration SMD 3-IN-1 LED

Pixel Density 160000 dots/m²

Pixel Pitch 2.5 mm

Pixel Pitch Category P2.5

Protection Level Front protection level IP5x

Resolution 256 × 192

8.8 kg (19.4 lb.)

Display

Brightness Uniformity ≥ 97%

Color Temperature 3000 K to 10000 K adjustable

Color Uniformity ≤ ± 0.003Cx, Cy

Contrast Ratio ≥ 5000:1

Viewing Angle Horizontal 160°, vertical 160°

White Balance 600 cd/m²

Brightness

Processing Performance

Display Color 281 trillion

Driving Method Constant current driving

Frame Frequency 60 Hz

Grey Level 16 bit

Refresh Rate 3840 Hz

Working Environment

Storage Humidity 10% to 80%RH

Storage Temperature -20 °C to 60 °C (-4 °F to 140 °F)

Working Humidity 10% to 80%RH

Working Temperature -10 °C to 40 °C (14 °F to 104 °F)
