

Technical Specs:

Model : E6520

Display

Diagonal Size (inch) : 65

Glass : Anti-glare, Tempered

Bonding : Zero parallax

Viewing Angle : 178°(H/V)

Aspect Ratio : 16:09

Backlight : DLED

Resolution : 3840 × 2160

Contrast Ratio : 1200:01:00

Color Depth : 1.07B(10bit)

Color Gamut (typ.) : 72% NTSC

Color Accuracy : Delta E ≤ 2

Refresh Rate : 60Hz

Response time : 8ms

Brightness (typ.) : Interactivity

Touch Sensor : Infrared (IR)

Touch Tool : Finger,Gesture,Stylus

Multitouch Capabilities : Up to 40 touch points (OS dependent)

Response Time : ≤ 10ms

Touch Accuracy : ±1.5mm

Object Recognition Range : ≥ 3mm

Stylus Type : Passive dual nibs

Supported Operating System (Touch Return) : Windows10 / Windows8 / Windows7 / WindowsXP / Android / Linux / Mac OS X / Chrome OS

Built-in System

Operating System : Android 11.0

RAM : 4GB

ROM : 32GB

CPU : 2.0GHz quad core ARM A55

GPU : Mali-G52 MP2

Software

Screen Share : Yes

DMS : Yes

On Board Apps : Browser, Cloud Drive, System Keeper, Note, Palette, Annotate, Timer, Screen Record, Split Screen, etc.

Power

Power Supply : AC 100~240V 50/60Hz

Power Consumption (standby) : ≤ 0.5W

Power Consumption (maximum) : 400W (including OPS)

Speaker

Sound Channel : 2

Power Output : 2 × 12w

Connectivity

OPS Slot : Yes, 3840 × 2160 @ 60fps

OPS Compatible : OPS62A

Wired : 1000baseT RJ45 × 2

Wi-Fi : 2.4Ghz, 5Ghz band ; 802.11ac/b/g/n/a/ax

HDMI : HDMI 2.0 In × 3 ; HDMI Out × 1 (Up to 4K @ 60fps)

Touch : USB Type-B × 2

Control : RS-232 × 1

Analog : VGA In × 1

Audio : Audio In × 1; Audio Out × 1; S/PDIF Out × 1

USB Type-A : USB 3.0 × 4; USB 2.0 × 1

Multifunction Port : USB Type-C × 1

Accessory

3m Power Cord : × 1

1.4m HDMI Cable : × 1

5m USB Touch Cable (Type A-B) : × 1

1.8m USB Type-C Cable : × 1

Remote Control : × 1

Wall Mount : × 1

Stylus : × 2

Wireless Adapter : × 1

Physical Specification

Dimension (W × H × D) : 1488.1 × 896.3 × 88.3mm

Shipping Dimension (W × H × D) : 1628 × 1024 × 208mm

VESA : 600 × 400mm, M8 × 25mm

Net Weight : 35.50 Kg

Gross Weight : 45.80 Kg

Environment

Operating Temperature : 0°C-40°C

Storage Temperature : -20°C-60°C

Operating Humidity : 10%-90% RH

Storage Humidity : 10%-90% RH