

PANEL

Screen Size	65"
Panel Technology	IPS
Back Light Type	Edge
Aspect Ratio	16 : 9
Native Resolution	3840 x 2160 (UHD)
Refresh Rate	60Hz
Brightness	500nit (Typ.)
Contrast Ratio	1,100:1
Dynamic CR	1,000,000:1
Color gamut	BT709 95%
Viewing Angle(H x V)	178 X 178
Color Depth	10bit(D), 1.07Billion colors
Response Time	8ms (G to G)
Surface Treatment(Haze)	28%
Life time	50,000Hrs (Min.)
Operation Hours (Hours/Day)	24/7
Portrait / Landscape	Yes / Yes

CONNECTIVITY

Input	HDMI (3, HDMI1/HDMI2 : HDCP 2.2/1.4, HDMI3 : HDCP 1.4), DP (1, HDCP2.2/1.3), DVI-D (HDCP1.4), Audio In, RS232C IN (1, 4pin Phone-jack), RJ45(LAN), IR IN, USB2.0 Type A(1)
Output	HDMI Out, Audio Out, RS232C OUT (1, 4pin Phone-jack)

MECHANICAL SPECIFICATION

Bezel Color	Black
Bezel Width	T/R/L: 9.9mm, B: 14.4mm
Weight(Head)	28.2Kg
Weight(Head+Stand)	28.8Kg
Packed Weight	35.0Kg
Monitor Dimension(W x H x D)	1453.3 x 844.0 x 39.9mm (with LG Logo)
Monitor Dimensions with Stand(W x H x D)	1453.3 x 893.1 x 290.0mm
Carton Dimensions(W x H x D) (Box outer size)	1600.0 x 1095.0 x 175.0mm
VESA™ Standard Mount Interface	300 x 300

KEY FEATURE

Key features	Internal Memory 16 GB, Built-in Wi-Fi, Temperature Sensor, Auto Brightness sensor, Acceleration(Gyro) Sensor, Local Key Operation, webOS6.0, Embedded CMS (Local Contents Scheduling, Group Manager), USB Plug & Play, Fail over, Background Image (Bootimg Logo Image, No Signal Image), Sync Mode (RS-232C Sync, Local Network Sync), Multi-screen (PIP, PBP (4)), Screen Share, Video Tag (4), Play via URL, Rotation (Screen Rotation, External Input Rotation), Gapless Playback, Tile Mode Setting (Max. 15 x 15), Setting Data Cloning, SNMP, ISM Method, Auto Set ID, Status Mailing, Control Manager, 3rd Party Compatibility (Crestron
---------------------	--

Connected), Power (Smart Energy Saving, PM mode, Wake on LAN, Network Ready), Beacon, HDMI-CEC, SI Server Setting, webRTC, Pro:Idiom

ENVIRONMENT CONDITIONS

Operation Temperature 0 °C to 40 °C

Operation Humidity 10 % to 80 %

POWER

Power Supply AC 100-240V~, 50/60Hz

Power Type Built-In Power

POWER CONSUMPTION

Typ. 130W

Max. 190W

BTU (British Thermal Unit) 444 BTU/Hr(Typ.), 649 BTU/Hr(Max.)

Smart Energy Saving(~70%) 91W

DPM 0.5W

Power off 0.5W

SOUND

Speaker Yes

CERTIFICATION

Safety CB / NRTL

EMC	FCC Class "A" / CE / KC
------------	-------------------------

ErP / Energy Star	Yes (NewErP) / Yes
--------------------------	--------------------

OPS COMPATIBILITY

OPS Type Compatible	Yes
----------------------------	-----

SOFTWARE COMPATIBILITY

SuperSign CMS	Yes
----------------------	-----

SuperSign Control / Control+	Yes / Yes
-------------------------------------	-----------

SuperSign WB	Yes
---------------------	-----

SuperSign Media Editor	Yes
-------------------------------	-----

Mobile CMS	Yes
-------------------	-----

Signage 365 Care	Yes
-------------------------	-----

LANGUAGE

OSD	English, French, German, Spanish, Italian, Korean , Chinese(Simplified), Chinese(Original), Portugues(Brazil), Swedish, Finnish, Norwegian, Danish, Russian, Japanese, Portugues(Europe), Dutch, Czech, Greek, Turkish, Arabic
------------	---

ACCESSORY

Basic	Remote Controller(include battery 2ea), Power Cord, QSG, Regulation Book, Phone to RS232C Gender
--------------	---

Optional	Stand(ST-653T), Wall bracket(LSW350B), OPS Kit(KT-OPSF)
-----------------	---

SPECIAL FEATURE

Tilt(Facedown)

Yes (Max 30° degree, 30°C temperature, humidity 50%)

IP Rating

IP5X
