

SPECKTRON

DKS-43 AP

43" Digital Kiosk

- Capacitive multi-touch interactive display
- Freestanding slim line design
- Protective glass fascia & built-in speakers
- 43" Full HD Portrait Display
- Integrated Android system
- Supports superior video content & applications



FULL
HD



SLIM



USB
CONNECTIVITY



MULTI
TOUCH



RETAIL



LEISURE



HOSPITALITY



HEALTHCARE



GOVERNMENT



MALLS



AIRPORTS

DKS-43 AP



Specktron's 43" Digital Kiosk is the ideal solution for a variety of environments, such as hospitality, retail, airports & public spaces. Featuring Ultra HD resolution, 178°/178° wide-angle viewing, 350-nit brightness, 1300:1 contrast ratio, 24/7 operation, capacitive touch to deliver messages with vivid clarity in a sleek, slim design. Photo and video files can be played back using the Quad-core media player and 8GB of internal memory.

SPECIFICATIONS

| PANEL | | MAINBOARD FEATURES | |
|-----------------------|---|-------------------------|--|
| Panel Size | 43" | Operating system | Android 6.0 |
| Max-Resolution(H x W) | 1920 x 1080 | CPU | Quad Core, Cortex A-17 |
| Viewing angle | 178° | Memory | 2 GB DDR3 RAM |
| Display colors | 16.7 M | Storage | 8 GB |
| Brightness | 350 cd/m ² | Internet connection | Wi-Fi and LAN |
| Contrast ratio | 1300:1 | SD Card Support | Yes |
| Response time | 8ms | Google Play Support | Yes |
| Display model | 9:16 | Scheduled On/ Off power | Yes |
| 24/7 Operation | Yes | Inputs | HDMI-IN x 1, USB ports x 2, Touch x 1, RJ 45 x 1 |
| Speakers | 2 x 5W | Outputs | HDMI-OUT x 1 |
| TOUCH | | CMS | Supports pushing content and remote management of unit |
| Touch frame | PCAP | CERTIFICATIONS | |
| Touch points | 10 | CE | Yes |
| SUPPORT MODES | | | |
| Video format | AVI(H.264,DIVX,DIV,XVID), rm, rmvb, MKV(H.264, DIVX, DIVX(XVID)), WMV, MOV, MP4(H.264,MPEG,DIVX,XVID), DAT(VCD format), VOB(DVD format), PMP, MPEG, MPG, FLV(H.263, H.264), ASF, TS, TP, 3GP, MPG | RoHS | Yes |
| PRODUCT DIMENSIONS | | | |
| Audio format | MP3,WMA,MP2,OGG,ACM4A,MA4,FLAC,APE,3GP,WAV. | Dimensions | 1810 x 450 x 593 mm |
| Picture format | BMP/PNG/GIF/JPEG | Weight | 40 KG |
| Text format | PDF, WORD, PPT, TXT, EXCEL | Operating temperature | 0°C~50°C |
| POWER | | Operating humidity | 10%~90% |
| Power Supply | AC 100~240V 50 / 60 Hz | Storage temperature | -20°C~60°C |
| Power Consumption | 100W | Storage humidity | 10%~90% |
| Standby | <SW | | |

*Model subject to availability in your region.