

DMInteract® SMART DUAL SIDED HANGING SIGNAGE DISPLAY

Dual Sided 4K OR FHD Resolution With High Brightness Built-In Android OS With Wire Rope Ceiling

SIZES: 43", 49, 55"

PRODUCT OVERVIEW

TRANSFORM YOUR ADVERTISING AND INFORMATION DISPLAY WITH THE DMINTERACT DM-DS43HS, DM-DS49HS, AND DM-DS55HS DUAL-SIDED DIGITAL SIGNAGE DISPLAYS. DESIGNED FOR HIGH-IMPACT VISIBILITY, THESE PROFESSIONAL-GRADE DISPLAYS FEATURE A DUAL-SIDED LED PANEL, ENSURING MAXIMUM EXPOSURE FROM BOTH ANGLES. WHETHER INSTALLED IN SHOPPING MALLS, TRANSPORTATION HUBS, OR CORPORATE SETTINGS, THEIR 700-NIT BRIGHTNESS DELIVERS STUNNING CLARITY EVEN IN WELL-LIT ENVIRONMENTS. WITH A 4K UHD RESOLUTION FOR THE 55-INCH MODEL AND FULL HD FOR 43-INCH AND 49-INCH MODELS, CONTENT APPEARS CRISP AND VIBRANT.





POWERED BY A QUAD-CORE CORTEX-A55 PROCESSOR WITH 2GB DDR3 RAM AND ANDROID 11, THIS SIGNAGE SEAMLESS OFFERS OPERATION SUPPORTS A WIDE RANGE OF MULTIMEDIA ITS FORMATS. ROBUST WITHSTANDS EXTREME TEMPERATURES FROM -20°C TO 60°C, MAKING IT IDEAL FOR INDOOR AND SEMI-OUTDOOR APPLICATIONS. EQUIPPED WITH WI-FI, RJ45, DUAL USB 3.0 PORTS, AND A MICROSD SLOT. PROVIDES ΙT **FLEXIBLE** CONNECTIVITY OPTIONS. CE, FCC, AND ROHS CERTIFIED, THE DMINTERACT DUAL-SIDED DIGITAL SIGNAGE DISPLAY IS THE PERFECT SOLUTION FOR BUSINESSES SEEKING HIGH-QUALITY, EFFICIENT, AND ATTENTION-GRABBING DIGITAL SIGNAGE.

TECHNICAL HIGHLIGHTS:

Brand Name:	DMInteract [®]		
Model Number:	DM-DS43HS	DM-DS49HS	DM-DS55HS
Panel Type:	LCD		
Resolution:	1920 x 1080	1920 x 1080	3840 x 2160
Backlight:	LED		
Brightness:	Side A = 700nits & Side B = 700nits		
Contrast Ratio:	1200 : 1		
Color Depth:	8 bits		
Response Time:	8ms (typ.)		
Viewing Angle:	178° / 178°		
Light Life Time:	50,000 hrs (typ.)		
Processor:	Quad-Core Cortex-A55 Up To 2.0GHz		
RAM:	2GB DDR3		
Graphics:	Mali-G52		
ROM:	EMMC 16GB		
IO Ports:	USB3.0 x 2, Micro SD Slot x 1		
Operating System:	Android 11		
Network:	WLAN 802.11 b/g/n (2.4GHz), RJ45		

TECHNICAL HIGHLIGHTS:

Brand Name:	DMInteract [®]		
Model Number:	DM-DS43HS	DM-DS49HS	DM-DS55HS
Multimedia:	H.264 encoder/decoder, MPEG-1/2/4, H.263,H.264 MVC, AVS, VC-1, VP8/6, RV		
Power Supply:	External		
Rated Voltage:	100 V ~ 240 V, 50Hz / 60Hz		
Language:	English		
Operating Temperature:	-20° C ~ 60° C		
Storage Temperature:	-10° C ~ 60° C		
Humidity:	10% ~ 80% RH Non-Condensing		
Certification:	CE, FCC & RoHS		
Orientation:	Portrait		
Cabinet Color:	Black		



SPECIAL OFFER







www.dubaimachines.com



DEALER ADDRESS:

Showroom G-02, IT Plaza, Dubai Silicon Oasis, Dubai, United Arab Emirates



CANADA OFFICE:

DMInteract Inc 801 Dundas Street East, Unit #D6, Mississauga, Ontario, L4Y 4G9



CONTACT NUMBER:

+971-4-3360300 - (Dubai Office) 437-880-7712 - (Mississauga Office)



EMAIL ADDRESS:

info@dminteract.com