

	SPEC_ITEM_LOCAL	Value
Display	Diagonal Size	65"
	Panel Type	ADS
	Resolution	3,840 x 2,160
	Pixel Pitch (HxV)	372(H)x372(V)
	Brightness (Typ)	400 nit
	Contrast Ratio	1,200:1
	Viewing Angle (H/V)	178/178
	Response Time	8ms
	Colour Gamut	72%
	Glass Haze	25%
	H-Scanning Frequency	135KHz
	Maximum Pixel Frequency	78MHz
	V-Scanning Frequency	60Hz
	Operation Time Support	12/7
Connectivity	HDMI In	3
	Version of HDMI	2
	Version of HDCP	2.1
	USB	5 (2.0 X1, 3.0X4)
	IR In	Yes
	Audio In	Stereo Mini Jack
	Audio Out	Stereo Mini Jack
	Video Out	Yes
	RS232 In	Yes
	RS232 Out	Yes
	RJ45 In	Yes
	RJ45 Out	Yes
	WiFi	Yes
	Bluetooth [®]	Yes
Power	Power Supply	AC100-240V 50/60Hz
	Power Consumption (On Mode)	385W
	Power Consumption (Sleep Mode)	0.5W↓
Dimension	Set Dimension (WxHxD)	1488 x 897 x 88 mm
	Package Dimension (WxHxD)	1628 x 1024 x 208 mm
Weight	Set Weight	33.9 kg
	Package Weight	42.9 kg
Operation Conditions	Temperature	0°C~40°C
	Humidity	10 ~ 90%
	VESA Mount	600 x 400 mm
Mechanical Specification	Bezel Width	16.4mm(U), 16.4mm(L/R), 44.9mm(B)
	Bezel Color	Space Gray
	Frame Material	Non-Glossy
Optional Feature	Touch	Yes

SoC	OS Version	Android-13
	Flash Memory Size	64GB
Touch	Touch Technology	IR
	EMC	Part 15, Subpart B Class A KS C9832, KS C9835
Certification and Compliance	EMC	EN55032:2015/A11:2020/A1:2020 EN
	Safety	IEC 62368-1 Edition 3&IEC 60950-1 UL62368-1 edition 3 GB4943.1-2022 PSB+ IEC 62368-1 NOM-019 K 62368 IRAM+ IEC 62368-1 EAC+ IEC 62368-1 INMETRO+ IEC 62368-1 SASO+ IEC 62368-1 BSMI+ IEC 62368-1 IEC 62368-1/AS/NZS 62368-1 IEC60950-1 / IS13252