

DMInteract®

178° VIEW OF ANGLE




SIZES: 46" , 55" , 65"



Original Brand Panel



4K display



Ultra Thin Bezel



Free Splicing

ULTRA-NARROW BEZELS (0.00MM, 0.88MM, 1.7MM, 1.8MM, OR 3.5MM)

DMInteract®
Ultra Narrow Bezel
4K LCD VIDEO WALL



www.dubaimachines.com



info@dubaimachines.com



Showroom G-02, IT Plaza, Dubai Silicon Oasis,



Dubai, United Arab Emirates

DMInteract® ULTRA NARROW BEZEL 4K LCD VIDEO WALL

The **DMInteract** Video Wall Display offers a seamless and immersive visual experience with multiple screen size options, including **46"**, **55"**, and **65"**. It features **Ultra-Narrow Bezels (0.00mm, 0.88mm, 1.7mm, 1.8mm, or 3.5mm)** for nearly gapless splicing, **Full HD resolution with 4K support, 500 nits brightness**, and a **178° wide viewing angle**. Designed for durability, it has a **60,000-hour lifespan** and supports various input interfaces like **HDMI, VGA, DVI, and USB**. Advanced control options include **RS232, remote control, WiFi, and smartphone compatibility**, making it a perfect choice for modern digital signage and control room applications.



WIDE VIEWING, MAXIMUM ENGAGEMENT

SIZES: 46" , 55" , 65"



Wall-Mount



Floor-Stand



Cabinet-Type



Hydraulic Front Maintenance



Curved-Installation

PRODUCT FEATURES

- **DMInteract** 4K Video Walls boast an industrial design with 80,000 hours of continuous operation for stable performance.
- Experience high resolution, high contrast, and a wide viewing angle, ensuring exceptional visual quality.
- The slim design of the video walls features narrow borders, with bilateral stitching measuring only 0.88mm.
- Employing a direct-type LED backlight system, our video walls deliver optimal brightness and clarity.
- With a built-in mosaic controller, these video walls enable seamless image mosaic displays.
- The inclusion of a 3D digital image processing kernel ensures precise monitoring of intricate details.
- Benefit from the image signal gain function for enhanced stability and accurate image control.
- Achieve image restoration capabilities, contributing to improved system reliability.
- Enjoy versatility with various signal interfaces, supporting a wide range of signal input and output options for enhanced connectivity.

DISPLAY PARAMETERS

Sizes: 46 inch, 55 inch, 65 inch

Type: DID LCD Panel

Resolution: 4K 3840x2160

Brightness: 500 nits

Contrast Ratio: 4000:1



TECHNICAL HIGHLIGHTS

Brand Name	DMInteract®
Multiple Screen Sizes	46 inches, 55 inches, and 65 inches
Splicing Gap	0.00mm, 0.88mm, 1.7mm, 1.8mm or 3.5mm
Backlight	LED
Aspect Ratio	16:9
Contrast Ratio	4500:1
Max Resolution	1920×1080 (Supported 4K)
Brightness	500cd/m ²
Color Saturation:	97%
Glass	Tempered Glass
Response Time:	6ms
Viewing Angle	178°
Service Life	About 60,000 Hours

TECHNICAL HIGHLIGHTS

Panel Color	Black
Signal Format	PAL/NTSC Adapting 480I, 576I, 720I, 720P, 1080I, 1080P
Interface Input	Power Connector, VGA, DVI, HDMI, CVBS, USB
Interface Output	CVBS, DVI
Control Port Input	Serial Port (RS232)
Control Port Output	Serial Port (RS232) x 2
Panel Control	Remote Control
Third Party Control	Wi-Fi, Smartphone, iPad (Customized)
Operating Power	≤200W
Standby Power	≤3W
Language	Multi-Language
Operating Temperature	0°C~50°C
Storage Temperature	-10°C~60°C



SPECIAL OFFER

ORDER NOW



CONTACT US



DEALER ADDRESS:

Showroom G-02, IT Plaza, Dubai Silicon Oasis, Dubai, United Arab Emirates



CANADA OFFICE:

DMInteract Inc 801 Dundas Street East, Unit #D6, Mississauga, Ontario, L4Y 4G9



CONTACT NUMBER:

+971-4-3360300 - (Dubai Office)
437-880-7712 - (Mississauga Office)



EMAIL ADDRESS:

info@dubaimachines.com | info@dminteract.com