# HYUNDAI IT Interactive Board Installation Cases

Corporate - Conference room
Location: Microsoft, Korea
Product: 84" Interactive Board
Application: Briefing and Meeting

Corporate - Meeting room
Location: Mitsui, Japan
Product: 84" Interactive Board
Application: Briefing and Meeting

Broadcasting studio
Location: KBS Main Hall, Korea
Product: 84", 70" Interactive Board
Application: Exhibition & Broadcast

Broadcasting studio
Location: SBS Studio, Korea
Product: 84" Interactive Board
Application: Broadcast Entertain.news

Roadshow
Location: Jakarta Stock Exchange, Indonesia (JSX)
Product: 65" Interactive Board
Application: Display Exhibition

Corporate - Conference room
Location: SK Research Institute, Korea
Product: 84" Interactive Board
Application: Briefing and Meeting

School - Class room
Location: Elementary School, Korea
Product: 84", 70" Interactive Board
Application: Smart Class

Hospital - Lab
Location: Severance Hospital, Korea
Product: 70" Interactive Board
Application: Research and Meeting

Coffee chain - Conference room
Location: Marley Coffee, Seoul
Product: 84" Interactive Board
Application: Meeting & Ad screen

Corporate - Conference room
Location: White Interactive, Dubai
Product: 84" Interactive Board
Application: Briefing and Meeting

Lecture room
Location: FLACSO University, Ecuador
Product: 84" Interactive Board
Application: Lecturing

Corporate - Lab
Location: IBM, Bangalore, India
Product: 84" Interactive Board
Application: Research and Meeting

Hyundai Interactive Board

Information
more than your imagination

Meet the new world with Hyundai Interactive Board
All existing business, education and life are renewed with a single touch

HYUNDAI IT

HEAD OFFICE
HYUNDAI IT CO., LTD.
S-20 Garden5 Tool 8F, Chungmin-ro,
Songpa-gu, Seoul, 138-962
The Republic of Korea
Tel : +82 70 7008 0151
Fax : +82 70 7008 0132
E-mail : ssoh@hyundaiit.com
www.hdit.co.kr

HYUNDAI IT
AMERICA CORP.
2051 Junction AVE., Suite 112
San Jose, CA 95131, USA
Tel : +1 408 954 8920
Fax : +1 408 954 8924
E-mail : sales@hyundaita.com
www.hyundaiit.com

HYUNDAI IT
EUROPE GMBH
Borsig Str. 11-13, 65205
Wiesbaden, Germany
Tel : +49 (0)6122 70342 10
Fax : +49 (0)6103 38878 110
E-mail : sales@hyundaiit.eu
www.hyundaiit.eu

HYUNDAI IT
JAPAN
Kawaziri Bldg 2F,
534 Waseda Tsurumakicho,
Shinjuku-ku, Tokyo, Japan
Tel : +81 3 6273 9652
Fax : +81 3 6273 9653
E-mail : sales@hyundaiit.co.jp
www.hyundaiit.com

FEATURES

- Touch Screen Function
- 178° Wide Viewing Angle
- High Resolution
- Anti-Glare Coating Tempered Glass
- Auto Brightness Sensor
- Easy Access with Front Input Ports
- Meeting Mate Software
- Quick Start Hot Key
- Real Handwriting

Make a difference with simple tip of your fingers

Everything will become simple and intuitive with Hyundai Interactive Board. Only few steps are needed to write, erase and to share the contents. Many convenient features are available and easy to apply. One finger will be enough to become the smartest.

GENERAL SPECIFICATIONS

IR Touch / PCAP Touch

Product Type		IR Touch UHD			IR Touch FHD		SMART OUTDOOR
Model		S75UAEI	S84UAEI	S98UAEI	E42AL	S55FAEI	Q557MSI
Display Panel	Screen Size	75"	84"	98"	42"	55"	55"
	Active Display Area (mm)	1650.2 x 928.3	1860.5 x 1046.5	2158.9 x 1214.4	930.2 x 523.3	1209.6 x 680.4	1209.6 x 680.4
	Resolution	3840 x 2160			1920 x 1080		1920 x 1080
	Brightness (cd/㎡, typ.)	450	420	500	500	350	2500
	Response Time (ms, GTG)	6	5	8	8	8	8
	Life Time (hours)	50,000			50,000		50,000
Touch Screen	Multi Touch	10			2		10
	Operating Systems	Windows, Linux , Mac			Windows, Linux		Windows, Linux , Mac
Resolution		3840 x 2160			1920 x 1080		1920 x 1080
Connectivity & Control	Input	1 x HDMI(2.0)	3 x HDMI(1.4)	2 x USB	1x DP			1x VGA (D-Sub)	2x HDMI	1x DVI	1 x USB 1x PC Audio	1x S232C	1x VGA (D-Sub)	4 x HDMI	1x DVI	2 x USB 1x PC Audio	1x RS232C	1x VGA (D-Sub)	1x HDMI	1x DVI	1x RS232C
	Output	1 x Audio Line out	Speaker (10Wx2CH)			1x DVI	1x RS232C	1 x Audio Line out	Speaker (10Wx2CH)		-
	Power Input Voltage (VAC)	100 - 240					100 - 240
	Power Consumption (w, typ)	310	450	475	105	150	500
	Auto Cooling System	Fanless			Yes	Fanless	Yes
	Auto Power Control (DPMS)			Yes			Yes
Feature	Tempered Glass (mm)	4, Anti-Glare		5, Anti-Glare	3, Anti-Glare		8, Anti-Glare
	Auto Brightness Sensor		No		Yes		Yes
Mechanical (Standard)	Dimension(mm) Set (W x H x L)	1745 x 1043 x 94	1955 x 1161 x 90	2258 x 1334 x 108	1035 x 640 x 60	1310 x 798 x 60	1334 x 820 x210 (With Wall Frame)
	Weight (kg) Set Weight	78	102	144	29	45	120
Environmental conditions	Temperature (°C)	0 - 40			0 - 40		-30 – 50
	Humidity (%)	20 - 80			20 - 80		20 - 80

Camera Touch

Product Type		Camera Touch UHD			Camera Touch FHD		
Model		S65UBEC	S75UBEC	S84UBEC	S65FBSC	S70FBSC	S84FBSC
Display Panel	Screen Size	65"	75"	84"	65"	70"	84"
	Active Display Area (mm)	1428.5 x 803.5	1650.2 x 928.3	1860.5 x 1046.5	1428.5 x 803.5	1538.9 x 865.6	1860.5 x 1046.5
	Resolution	3840 x 2160			1920 x 1080		3840 x 2160
	Brightness (cd/㎡, typ.)	450		420	350	450	420
	Response Time (ms, GTG)	5	6	5	6.5	8	5
	Life Time (hours)	50,000			30,000	50,000	
Touch Screen	Multi Touch	4			4		
	Operating Systems	Windows, Linux, Mac			Windows, Linux, Mac		
Resolution		3840 x 2160			1920 x 1080		
Connectivity & Control	Input	1 x DP(1.2)	1 x HDMI(2.0)	3 x HDMI(1.4)	2 x USB			1x VGA (D-Sub)	1 x HDMI(2.0)	3 x HDMI(1.4)	1x DVI	1x Component	2 x USB	1x PC Audio	1x Component Audio	1x RS232C		
	Output	1 x Audio Line out	Speaker (10Wx2CH)			1x DVI	1x RS232C	1 x Audio Line out	Speaker (10Wx2CH)		
	Power Input Voltage (VAC)	100 - 240			100 - 240		
	Power Consumption (w, typ)	180	310	450	140	310	450
	Auto Cooling System	Fanless			Fanless		
	Auto Power Control (DPMS)	Yes			Yes		
Feature	Tempered Glass (mm)	5, Anti-Glare			5, Anti-Glare		
	Auto Brightness Sensor	Yes			Yes		
Mechanical (Standard)	Set (W x H x L)	1593 x 968 x 92	1814 x 1092 x 92	2028 x 1214 x 92	1593 x 968 x 92	1717 x 1039 x 92	2028 x 1214 x 92
	Set Weight (kg)	69	97	99	72	74	99
Environmental conditions	Temperature (°C)	0 - 40			0 - 40		
	Humidity (%)	20 - 80			20 - 80		

* Specifications and designs are subject to change without notice.

Efficiency and Innovation

No need to bring printed materials or to connect your external device. Connect directly with your USB memory, and present your materials, and send over the annotating materials via email. Maximize your work efficiency by eliminating unnecessary steps.

Various Connections

Build a flexible and reliable collaboration environment with various connectivity between interactive board and other external devices.

Faster and more Convenient

With the user-friendly interface, even a neophyte can easily operate Interactive Board. For user convenience, we have place hotkeys at the edge of panel facilitating the mode shifting.

Technology Acclaimed by Global Companies

With the user-friendly interface, even a neophyte can easily operate Interactive Board. For user convenience, we have place hotkeys at the edge of panel facilitating the mode shifting.

Write and Save on Directly on Office Files

You can now directly write and save on images, video and documents files. Expand, edit and save directly on MS Office files. Our solution has been tailor-made to be a complementary solution to office documents.

Most Sophisticated Handwriting

* Real Handwriting on Hyundai Interactive Board.

We have developed the most sophisticate annotating software. You can now express every single detail without any distortion.

Conference Anytime, Anywhere

Using RemoteMate you can now easily attend a meeting regardless the time and location. It's not just a face-to-face meeting, but also sharing opinions while looking at the same materials.

Updated Software

Hyundai Interactive board maintains the performance and stability over its entire lifetime. Most optimal software developed by us, automatic update option is now available. The users can always use the up-to-date software without any additional cost.