STU-530 / STU-430



Flat, robust and secure: STU-530 and STU-430 signature pads

The STU-530 brings colour to counters and check-outs. With its 5" high resolution colour LCD screen, the STU-530 is the ideal signature pad for use at the POS or customer contact point. In addition to capturing handwritten signatures, it can be utilised for branding, marketing or advertising purposes, making it also a valid marketing tool. The Wacom pen can be tethered to the pad to prevent loss. The STU-530 is made for heavy stationary use.

The STU-430 is a small and robust, extremely durable signature pad. Its 4.5" monochrome screen is large enough to capture longer signatures as well as to accommodate software buttons in addition to the signature area. The transflective LCD can easily be read in varying light conditions. A hardened glass surface protects the LCD screen and is highly resistant to scratches. The integrated pen compartment doubles as a USB cable lock to prevent accidental disconnection of the cable.

Both signature pads feature a new thin design and a low profile, flat surface. The new design reflects the market requirements for modern, robust, ergonomic and reliable signature pads. They are equipped with Wacom's patented maintenance-free EMR technology, delivering 1024 pressure levels. For security, a data encryption is embedded in the signature pads (AES 256 / RSA 2048). Each unit is assigned a unique hardware ID in order to determine the exact unit that was used to capture a particular signature.









STU-530 STU-430

Windows® 8, 7, Vista, XP™ (excl. x64 version)

| 161.43 x 174.37 x 10.85 mm, 6.35 x 6.86 x 0.42 inch | | |
|---|--|--|
| 279 g | | |
| Dark grey | | |
| Black | | |
| Via USB, no additional power adapter required | | |
| 1.0 W maximum | | |
| USB 2.0 (Full-Speed) | | |
| Yes, blue light | | |
| | | |

| LCD Screen | | | |
|------------------------|---|--|--|
| Display type | Amorphous TFT LCD, colour, LED backlight | F-STN Positive Reflective | |
| Cover plate surface | Tempered glass | | |
| Screen diagonal | 108.0 x 64.8 mm (5.0 inch - 4.25 x 2.55 inch) | 96.0 x 60.0 mm (4.5 inch - 3.77 x 2.36 inch) | |
| Resolution | 800 x 480 pixels, WVGA | 320 x 200 pixels | |
| Pixel pitch H/V | 0.135 x 0.135 mm, 0.053 x 0.053 inch | 0.300 x 0.300 mm, 0.118 x 0.118 inch | |
| Viewing angles H/V | 140° / 140° | -/- | |
| Colours | True colour (16,7 million colours) | B/W | |
| Luminance (brightness) | 168 cd/m² (typ) | -/- | |
| Contrast ratio | 600:1 | -/- | |
| Response time | 20 ms | -/- | |
| Backlight lifetime | 20.000 hours | No Backlight | |

| Technology | Electromagenetic resonance (EMR) | | |
|-----------------------|--|------------------------------------|--|
| Active area | 108.0 x 64.8 mm, 4.25 x 2.55 inch | 95.98 x 59.98 mm, 3.77 x 2.36 incl | |
| Resolution | 2540 lpi (non-interpolated) | | |
| Coordinate accuracy | ± 0.5 mm / 0.02 inch (center) | | |
| Report rate | 200 points per sec. (non-interpolated), 800 4D coordinates | | |
| Pressure levels | 1024 (non-interpolated) | | |
| Reading height | 5 mm / 0.2 inch (center) | | |
| Pen storage | Integrated | | |
| Encryption | AES 256 bit encryption, RSA 2048 bit key exchange | | |
| Pen | Active EMR pen | | |
| Pen size (L x D) | 140.5 x 9.0 mm, 5.53 x 0.35 inch | | |
| Pen weight | 7 g | | |
| Pen tether opening | Yes | | |
| Pad identification | Unique ID | | |
| Connectivity security | USB cable locking system | | |
| Data security | Real time signature capture without internal pad memory | | |
| Anti-theft protection | Slot for Kensington locking system (3rd party) | | |

| Miscellaneous | | | |
|------------------------|---|--|--|
| Graphics card | Not needed | | |
| Software | Compatible with signature / E-signing software and | | |
| | Wacom's sign I pro PDF, C++, .Net and Java SDK/API available for developers | | |
| Package content | Signature pad (STU-530/G resp. STU-430/G), cordless and battery-free pen (UP-610A-89A-1), | | |
| | USB cable, (STJ-A-337; 3 m / 9.84 ft), quick start guide (UM-0558), pen tether (PKB-A038; nylon fiber, 50 cm / 19.7 inch) | | |
| Operating temperature, | +5°C to +40°C, +41°F to +104°F, (humidity 30% to 80% RH, no condensing) | | |
| relative humidity | +5 C to +40 C, +41 F to +104 F, (nutritative 30% to 60% hrt, 110 condensing) | | |
| Storage temperature, | -20°C to +60°C, -4°F to +140°F, (humidity 30% to 90% RH, no condensing) | | |
| relative humidity | -20 C to +00 C, -4 1 to +140 1, (number 50 % to 50 % h11, 110 condensing) | | |
| Warranty | 3 years depending on region and channel of purchase | | |



Supported operating systems