

Sleek, Slim, Free-Standing Display for Dynamic Advertising



EP4220



Free-standing dynamic advertising is easy with ViewSonic's EP4220—an ultra-slim 42" Full HD digital ePoster LED display. Retail and information messaging is easily broadcast via the display's internal media player, or by connecting your own media to the industry-standard HDMI or VGA input connections. ViewSonic's ePoster display can also be connected to a corporate network by adding a network capable media player. Security is achieved through the locking back cover. Compatible ViewSonic media players are available in both X86 and RISC (Linux) configurations. This display is ideal in highvisibility locations such as retail settings, hotel lobbies, banks and universities.

Features

- 42" Full HD electronic ePoster LED display
- Internal media player
- 4GB storage
- HDMI or VGA input connections

06102015



Sleek, Slim, Free-Standing Display for Dynamic Advertising



EP4220

Technical Specifications

Display	Panel Size	42"
	Type/Tech	TFT LCD Module with LED Backlight
	Display Area (mm)	930.24(H) x 523.26(V)
	Aspect Ratio	9:16
	Native Resolution	1080x1920
	Colors	16.7M
	Brightness	350 nits (typ.)
	Contrast Ratio	3000:1 Typ.
	Response Time	6.5ms
	Viewing Angles	H = 178, V = 178 typ.
	Backlight Life	30,000 Hours Typ.
	Surface Treatment	AG coating (3H)
	Orientation	Portrait
INPUT	HDMI	x1
	RGB / VGA	x1
	Audio	x1 PC audio(3.5 mm)
	RS232	x1
	SD/SDHC	SD/CF x1, (for expand storage)
USB	Type A	x1
SPEAKERS		2.5W x 2
COMPATIBILITY	RGB PC/HDMI PC	Refer to timing table
	HDMI	480i, 480p,720p,1080i,1080p
CONTROLS	Physical- Top OSD	PICTURE: Picture Mode, Color Temperature, Aspect Ratio, Noise Reduction, Screen AUDIO: Sound Mode, Balance, Auto Volume, Surround Sound, EQ TIME: Clock, On/Off Time, Time Volume, Display Mode, Display Mirror, User Reset, Software Version, Software Update (USB) OPTION: OSD Language, Subtitle Color, Subtitle BG Color, Subtitle Speed, Play Mode, Photo Time, Picture Slide Show, USB Copy Mode

06102015



Sleek, Slim, Free-Standing Display for Dynamic Advertising



EP4220

	Multimedia	JPG, MPEG 1/2/3, H.264, Xvid 1.00–AVI, MP4, WMA, MP3, M4A (AAC)
Power	Voltage	100-240VAC +/- 10% 50/60Hz Wide Range
	Consumption	180W (max.) < 0.5 W ("Off")
OPERATING CONDITIONS		
	Temperature (° C)	0°C to 45°C
	Humidity	10% ~ 85% non-condensing
DIMENSIONS (W x H x D)		
	Physical (inch / mm)	27.0 x 72.2 x 17.7 / 685 x 1835 x 450
	Packaging (inch / mm)	32.3 x 76.7 x 21.3 / 820 x 1950 x 540
WEIGHT		
	Net (lb / kg)	125 / 57
	Gross (lb / kg)	147 / 67
REGULATIONS		
		FCC
PACKAGE CONTENTS		
		1. EP4220 ePoster 2. power cable 3. VGA cable 4. remote control with batteries 5. Quick Start Guide 6. ViewSonic Wizard CD (with User Guide) *Actual content may differ from market to market

