

Key Features

Full HD 1080p for Superior Pixel
Performance | MHL functionality for easy
connection to mobile devices |
SuperClear® Image Enhancement
Technology with wide viewing angles |
ViewSonic Flicker-Free viewing for
improved eye comfort | ViewMode
settings for digital content



Product **Description**

The ViewSonic VX2263Smhl-W is a 22" (21.5" viewable) Full HD 1080p display designed for entertainment, gaming, and multimedia applications. An MHL port enables seamless connectivity, and simultaneous battery charging, of MHL-enabled mobile devices to facilitate easy content sharing and mobile gaming on a larger screen. Additional versatile connectivity options include HDMI and VGA ports for added convenience in traditional PC environments. In addition, ViewSonic's SuperClear® image enhancement technology delivers superior colour performance with excellent colour reproduction, while a 50M:1 MEGA Dynamic Contrast Ratio and integrated stereo speakers provide great multimedia and entertainment performance. Additional features include Eco-mode for increased energy savings, as well as a 100x100mm VESA mount for more flexible installation options. A premium design includes a frameless edge-to-edge glass faceplate and slim bezel beneath the glass, making the VX2263Smhl-W a stylish addition to any desktop.

Visit Us

www.viewsonic.com

| LCD | dataon |
|---------------------|---|
| Type: | 21.5" Wide Color a-Si TFT Active Matrix 1920x1080 LCD (AH-IPS Panel) |
| Display Area: | 21.5 inch |
| Optimum Resolution: | 1920x1080 |
| Contrast Ratio: | 1000:1 (typical), 50M:1 (maximum) |
| Brightness: | 250 cd/m ² (typ) |
| Viewing Angles: | 178°/178° (typ) |
| Response Time: | 2ms |
| Panel Surface: | Anti-Glare type, Hardness 3H |
| Light Source: | 30,000 Hrs |
| Colors: | 16.7M |
| VIDEO INPUT | |
| Analog: | RGB Analog (75 ohms, 0.7 / 1.0 Vp-p) |
| Digital: | HDMI (TMDS, 100ohms) |
| Frequency: | Fh: 24-82KHz; Fv: 50- 75Hz |
| Sync: | Separate Sync/Composite Sync/Sync on Green |
| COMPATIBILITY | |
| PC: | PC Compatibles (VGA up to 1920x1080 Non Interlaced) |
| Mac: | Power Mac (up to 1920x1080) |
| CONNECTOR | |
| Analog: | DB-15 x1 |
| Digital: | HDMI x1, HDMI/MHL x1 |
| Audio: | Out: 3.5mm plug x1; In:3.5mm plug x1 |
| Power: | External Adapter , 3-pin plug (CEE22) x1 |
| AUDIO | |
| Speakers: | 1.5 Watt (x2) |
| POWER | |
| Voltage: | AC 100-240V (Universal); 50/60 Hz |
| Consumption: | 20W; Optimize:17W; Conserve:14W |

WEIGHT

Net: 2.9 kg

REGULATIONS

CE EMC CB RoHS Green BOM List & RoHS DoC ErP REACH SVHC List & DoC WEEE WHQL Windows 8, BSMI, PSB

WALL MOUNT

VESA®100 x 100 mm

PACKAGE CONTENTS

Power Cable, Adaptor, D-Sub Video Cable, HDMI cable, Audio cable, Quick Start Guide, ViewSonic Wizard CD-ROM *Actual content may differ from market to market

Copyright © ViewSonic Corporation 2000-2017. All rights reserved. (06/21/2017 04:31:30 UTC)

 $32^{\circ}F \sim 104^{\circ}F / 0^{\circ}C \sim$

10% to 90% (no

498.8mm (width) x 387.7mm (height) x

164mm (depth)

condensation)

OPERATING CONDITIONS

Temperature:

DIMENSIONS

Humidity:

Physical: