

ViewSonic® LED DISPLAY **VX2409**

Key Features

Slim Bezel with Premium Glass Base | Full HD 1080p for Superior Pixel Performance | Planet-Friendly Mercury-Free LED Backlighting | Eco-mode Conserves More Energy | 20M:1 MEGA Dynamic Contrast Ratio



Product Description

The ViewSonic VX2409 is a 24" (23.6" viewable) Full HD LED display with premium glossy-finish, slim bezel design and stylish glass base, that features 1920 x 1080 resolution, 20M:1 DCR and 5ms response time to deliver crisp color performance. Equipped with DVI and D-Sub video inputs, it can easily connect to a PC or laptop for work in the office, web surfing, and entertainment. With an energy-efficient LED backlight and ECO mode, the VX2409 is also the environmentally friendly display choice. Plus, this display provides sRGB and Color Adjust functions, offering image reproduction quality that most closely matches the original image source. Flexible installation for homes and businesses is also ensured with a VESA-standard 75mm x 75mm mount.

Visit Us www.viewsonic.com

LCD

| | |
|---------------------|--------------------------------------------|
| Type: | 23.6" diagonal color active matrix TFT LCD |
| Display Area: | 23.6 inch |
| Optimum Resolution: | 1920x1080 |
| Contrast Ratio: | 1000 :1 (typical), 20M:1 (maximum) |
| Brightness: | 250 cd/m ² (typ) |
| Viewing Angles: | 170° / 160° |
| Response Time: | 5ms |
| Panel Surface: | Anti-Glare type, Hard-coating (3H) |
| Light Source: | 30000 Hrs (Min) |
| Colors: | 16.7 M |

VIDEO INPUT

| | |
|------------|--------------------------------------|
| Analog: | RGB Analog (75 ohms, 0.7 / 1.0 Vp-p) |
| Digital: | DVI (TMDS, 100 ohms) |
| Frequency: | Fh: 24-82KHz; Fv: 50-75Hz |
| Sync: | Separate Sync |

COMPATIBILITY

| | |
|------|-----------------------------------------------------|
| PC: | PC Compatibles (VGA up to 1920x1080 Non Interlaced) |
| Mac: | Power Mac (up to 1920x1080) |

CONNECTOR

| | |
|----------|---------------------------|
| Analog: | DB-15 x1 |
| Digital: | DVI-D x1 |
| Power: | External Power Adaptor x1 |

POWER

| | |
|--------------|-----------------------------------|
| Voltage: | AC 100-240V (Universal); 50/60 Hz |
| Consumption: | 24W; Optimize: 18W; Conserve: 15W |

OPERATING CONDITIONS

| | |
|--------------|------------------------------|
| Temperature: | 32°F to 104°F (0°C to 40°C) |
| Humidity: | 10% to 90% (no condensation) |

DIMENSIONS

| | |
|-----------|----------------------------------------------------|
| Physical: | 550.3mm (width) x 384.1mm (height) x 215mm (depth) |
|-----------|----------------------------------------------------|

WEIGHT

| | |
|------|--------|
| Net: | 3.6 kg |
|------|--------|

REGULATIONS

| | |
|------------|--|
| WEEE, RoHS | |
|------------|--|

WALL MOUNT

| | |
|-------------------|--|
| VESA® 75mm x 75mm | |
|-------------------|--|

PACKAGE CONTENTS

| |
|--------------------------------------------------|
| LCD Display |
| Adaptor (wall type) |
| VGA Cable |
| User Manual (hard copy) |
| *Actual content may differ from market to market |