Product Specifications

SM58® Cardioid Dynamic Microphone

Overview

The legendary SM58® is an industry-standard, highly versatile cardioid dynamic vocal microphone that is consistently the first choice of vocal performers around the globe. Even in extreme conditions, the SM58 is tailored to target the main sound source while minimizing background noise, delivering warm and clear vocal reproduction.

Features

- Frequency response tailored for vocals, with brightened midrange and bass rolloff
- Uniform cardioid pickup pattern isolates the main sound source and minimizes background noise
- Pneumatic shock-mount system cuts down handling noise
- Effective, built-in spherical wind and pop filter
 Supplied with break-resistant stand adapter which rotates 180 degrees
- Supplied with break-resistant stand adapter which rotates 180
 Legendary Shure quality, ruggedness and reliability
- Cardioid (unidirectional) dynamic
- Frequency response: 50 to 15,000 Hz

Available Models

SM58-LC	Includes Stand Adapter and Zippered Pouch
SM58-CN	Includes 7.6 m (25 ft) XLR-Male to XLR-Female Cable, Swivel Adapter and a Zippered Pouch
SM58S	Includes Integrated On/Off Switch, Swivel Adapter and a Zippered Pouch

Specifications

Туре	Dynamic		
Frequency Response	50 to 15,000 Hz		
Polar Pattern	Cardioid		
Sensitivity (at 1,000 Hz Open Circuit Voltage)	–54.5 dBV/Pa (1.85 mV) 1 Pa = 94 dB SPL		
Impedance	Rated impedance is 150Ω (300 Ω actual) for connection to microphone inputs rated low impedance		
Polarity	Positive pressure on diaphragm produces positive voltage on pin 2 with respect to pin 3.		
Case	Dark gray, enamel-painted, die cast metal; matte-finished, silver colored, spherical steel mesh grille		
Connector	Three-pin professional audio connector (male XLR type)		
Net Weight	298 grams (10.5 oz)		
Dimensions	162 mm (6-3/8 in.) L x 51 mm (2 in.) W		

Optional Accessories and Replacement Parts

A58WS	Windscreen	A55M	Isolation Mount	C25F	7.6 m Cable (25 ft)
A25D	Microphone Clip	A26M	Dual Mount	RK143G	Screen and Grille
R59	Cartridge	S37A, S39A	Desk Stand		

Polar pattern



------ 125 Hz ------ 500 Hz ---- 1000 Hz



----- 4000 Hz ---- 8000 Hz

Frequency response



SHURE® Legendary Performance™

SM58