

Dell P3418HW Specs

Display

| | |
|--------------------------|-------------------------------------|
| Size | 34" |
| Screen Area | 31.49 x 13.18" / 799.85 x 334.77 mm |
| Panel Type | IPS-Type LCD |
| Touchscreen | No |
| Resolution | 2560 x 1080 |
| Aspect Ratio | 21:9 |
| Pixels Per Inch (ppi) | 82 ppi |
| Finish | Matte |
| Hardness Rating | 3H |
| Maximum Brightness | 300 cd/m ² |
| Contrast Ratio | 1000:1 |
| Refresh Rate | 60 Hz |
| Adaptive Sync Technology | <i>None</i> |

| | |
|---------------------------|---------------------------------|
| Bit Depth / Color Support | 6-Bit+FRC (16.7 Million Colors) |
|---------------------------|---------------------------------|

| | |
|-------------|----------|
| Color Gamut | 99% sRGB |
|-------------|----------|

| | |
|---------------|--------------------|
| Response Time | 8 ms 5 ms (GtG) |
|---------------|--------------------|

| | |
|-----------|------------------|
| Dot Pitch | 0.312 x 0.310 mm |
|-----------|------------------|

Inputs / Outputs

| | |
|--------------|--|
| Connectivity | 2 x HDMI 1.4 1 x DisplayPort 1.2 1 x Mini DisplayPort 1 x 3.5 mm Output 4 x USB Type-A (USB 3.1 Gen 1) 1 x USB Type-B (USB 3.1 Gen 1) |
|--------------|--|

| | |
|--------------|------------------|
| HDCP Support | Yes, Version 1.4 |
|--------------|------------------|

| | |
|-------------------|---------------------|
| Built-In Speakers | Yes, 2 x 9 W |
|-------------------|---------------------|

Power

| | |
|-------------------|--|
| Power Consumption | 40 W (Typical) 120 W (Maximum) 0.5 W (Standby) |
|-------------------|--|

| | |
|----------------|-----------------------------------|
| AC Input Power | 100 to 240 VAC, 50 / 60 Hz at 4 A |
|----------------|-----------------------------------|

Environmental

| | |
|-----------------------|---------------------------|
| Operating Temperature | 32 to 104°F / 0 to 40°C |
| Storage Temperature | -4 to 140°F / -20 to 60°C |
| Operating Humidity | 10 to 80% |
| Storage Humidity | 5 to 90% |
| Operating Altitude | 12,000' / 3657 m |
| Storage Altitude | 40,000' / 12,192 m |
| Certifications | RoHS, as per Manufacturer |

Physical

| | |
|------------------------|--|
| Height Adjustment | 4.53" / 115 mm |
| Rotation Adjustment | <i>None</i> |
| Swivel Adjustment | 60° (-30 to 30°) |
| Tilt Adjustment | -5 to 21° |
| Mounting-Hole Pattern | 100 x 100 mm |
| Lock Slot | Yes |
| Dimensions (W x H x D) | 32.0 x 21.0 x 8.9" / 813.9 x 532.6 x 226.4 mm (with Stand) 32.0 x 14.5 x 2.0" / 813.9 x 368.1 x 51.3 mm (without Stand) |

| | |
|--------|--|
| Weight | 22.24 lb / 10.09 kg (With Stand) 15.01 lb / 6.81 kg (Without Stand) |
|--------|--|

Packaging Info

| | |
|----------------|----------|
| Package Weight | 32.95 lb |
|----------------|----------|

| | |
|------------------------|---------------|
| Box Dimensions (LxWxH) | 36 x 17 x 10" |
|------------------------|---------------|
